


ITAndroids Humanoid Robots Specifications for RoboCup 2022

Caroline Silva, Débora Ferreira, Eric Guerra, Francisco Silva, Gabriel Rocha, Gustavo Lima, Gustavo Pereira, Lucas Nogueira, Marcos Máximo, Otávio Ribas, Samuel Afonso, Thiago Origo, and Thiago Tonaco


Autonomous Computational Systems Lab (LAB-SCA)
Aeronautics Institute of Technology (ITA)
São José dos Campos, São Paulo, Brazil
{dfsbor,eric.guerra.07,fbrunodr,lincon.glds,gupereira97,ncostalucas,otaviohrguimaraes,samuel.afonsodesouza,tonaco.k.t22}@gmail.com
{carol.c.duarte,gabriel_rocha_neves,thiago.origo}@hotmail.com
mmaximo@ita.br
<http://www.itandroids.com.br>

1 Chape (4x)



Robot name	Chape
Height of the robot	530 mm (with football boots)
Weight of the robot	3.1 kg
Walking speed in cm/s (over grass)	30
Number of DoF	20 (2 neck + 3 per arm + 6 per leg)
Main computer	Intel NUC Core i5 @ 2.6 GHz dual core
Subcontroller	CMB v3 (designed by ITAndroids)
Camera	Logitech C920
IMU	MinIMU-9 (3-axis acc. + 3-axis gyro)
Servomotors	20 x Dynamixel MX-28AT
Battery	1300 mAh 4 cell LiPo (14.8–16.8 V)

2 Chape 2nd Generation (1x) – under development



Robot name	Chape 2nd Generation
Height of the robot	650 mm (with football boots)
Weight of the robot	≈ 4.5 kg
Walking speed in cm/s (over grass)	20
Number of DoF	20 (2 neck + 3 per arm + 6 per leg)
Main computer	Intel NUC Core i7 @ 2.6 GHz quad core
Vision Processing Unit (VPU)	Intel Movidius Neural Compute Stick 2
Subcontroller	CMB v4 (designed by ITAndroids)
Camera	Logitech BRIO
IMU	MinIMU-9 (3-axis acc. + 3-axis gyro)
Servomotors	MX-28AT (neck and arms) + XM540-W150-R (legs)
Battery	3000 mAh 4 cell LiPo (14.8–16.8 V)